

Previous editions  
are no longer valid

**TECHNICAL DATA SHEET**

02.01.2020

**ISOBUTANOL**

1 / 1

Isobutanol is transparent, water-insoluble liquid with characteristic odour.

**1. Quality characteristics**

Parameter	Unit	Value	Test method
Appearance	-	transparent liquid	<sup>1)</sup> BN-90/6191-79 p.5.3.4
Colour, Pt-Co scale	-	max. 5	ASTM D 1209
Density (20°C)	g/cm <sup>3</sup>	0.801 ÷ 0.804	densimeter
Isobutanol	%	min. 99.5	gas chromatography
Acetaldehydes as butyraldehyde	%	max. 0.05	our own method
Water	%	max. 0.10	K. Fischer
Acidity as acetic acid	%	max. 0.003	our own method

The parameters values given above can be changed if they were previously agreed between the producer and a customer.  
Remarks: <sup>1)</sup> BN = Branch standard.

**2. Application**

Isobutanol is mainly used as solvent for paints, lacquers and as a raw material in chemical industry.

**3. Transportation and package**

Rail tank cars, road tankers, PE containers (DPPL) or steel drums. The other packages can also be used if previously agreed between the producer and a customer.

Isobutanol should be transported according to RID / ADR regulations.

**4. Storage**

It is recommended to store isobutanol in steel tanks or drums at a temperature not higher than 30 [°C].  
Store according to SDS.